



0301 KSS 抗UV扎线带 UV RESISTANT NYLON CABLE TIE



材质：UL合格之NYLON 66，防火等级94V-2。

颜色：黑色。


特点：抗UV原料（抗紫外线），适合户外使用。

用法：将扎线带尾巴穿过头部，即可束紧。

※1.CVT-070W、CVT-100W带身设计薄软，能贴合头部，束紧较小电线。

※2.CV-180TW、CV-190TW尾端尖型设计。

※3.CV-200TW尾端有止滑点。



型 号 Item No.		长 L		宽 W	最大束线径 Max.Bundle Dia.	承受力 Min LoopTensile Strength	
100pcs	1000pcs	mm	inch	mm	mm	lbs	kgs
CV-060W	CV-060KW	63.7	2 1/2"	2.4	11	18	8
※1 CVT-070W	CVT-070KW	71	2 13/16"	1.6	16	7	3
CV-075W	CV-075KW	75	3"	2.4	15	18	8
CV-080W	CV-080KW	80	3 1/8"	2.5	16	18	8
CV-094W	CV-094KW	96	3 3/4"	2.5	21	18	8
CV-100W	CV-100KW	100	4"	2.5	22	18	8
※1 CVT-100W	CVT-100KW	103	4"	1.95	22	11	5
CV-120SW	CV-120SKW	120	4 3/4"	2.5	28	18	8
CV-120W	CV-120KW	120	4 3/4"	3.2	27	40	18
CV-120LW	CV-120LKW	120	4 3/4"	4.8	27	50	22
CV-120LLW	CV-120LLKW	120	4 3/4"	7.6	22	120	55
CV-140SW	CV-140SKW	142	5 1/2"	2.5	35	18	8
CV-140W	CV-140KW	142	5 1/2"	3.2	34	40	18
CV-150SW	CV-150SKW	155	6 1/8"	2.5	39	18	8
CV-150W	CV-150KW	150	6"	3.6	36	40	18
CV-150LW	CV-150LKW	150	6"	7.6	32	120	55
CV-160LW	CV-160LKW	160	6 1/4"	4.8	39	50	22
CV-165W	CV-165KW	165	6 1/2"	2.5	43	18	8
CV-180W	CV-180KW	180	7"	3.6	46	40	18
※2 CV-180TW	CV-180TKW	180	7"	3.6	46	40	18
CV-190W	CV-190KW	190	7 1/2"	4.8	49	50	22
※2 CV-190TW	CV-190TKW	190	7 1/2"	4.8	49	50	22
CV-200MW	CV-200MKW	203	8"	2.5	55	18	8
CV-200SW	CV-200SKW	203	8"	3.2	53	40	18
CV-200AW	CV-200AKW	203	8"	3.6	52	40	18
CV-200W	CV-200KW	203	8"	4.6	52	50	22
※3 CV-200TW	CV-200TKW	203	8"	4.6	52	50	22
CV-200DW	CV-200DKW	203	8"	4.8	52	50	22
CV-200LW	CV-200LKW	203	8"	7.6	52	120	55
CV-240LW	CV-240LKW	240	9 7/16"	7.6	61	120	55

（接下页）

0301 KSS 抗UV扎线带 UV RESISTANT NYLON CABLE TIE



型号 Item No.		长 L		宽 W	最大束线径 Max.Bundle Dia.	承受力 Min LoopTensile Strength	
100pcs	1000pcs	mm	inch	mm	mm	lbs	kgs
CV-250SW	CV-250SKW	250	10"	2.5	68	18	8
CV-250MW	CV-250MKW	250	10"	3.6	68	40	18
CV-250W	CV-250KW	250	10"	4.8	68	50	22
CV-250LW		250	10"	7.6	64	120	55
CV-265W	CV-265KW	265	10 1/2"	3.6	73	40	18
CV-280W	CV-280KW	280	11"	4.8	77	50	22
CV-292W	CV-292KW	292	11 1/2"	3.6	82	40	18
CV-300MW		300	11 7/8"	2.5	80	18	8
CV-300SW		300	11 7/8"	4.8	83	50	22
CV-300W		300	11 7/8"	7.6	80	120	55
CV-310W		310	12"	4.8	86	50	22
CV-330W		330	13"	3.6	93	40	18
CV-340W		340	13 1/2"	7.6	92	120	55
CV-350W		350	13 3/4"	4.6	98	50	22
CV-360W		360	14 3/16"	7.6	99	120	55
CV-368SW		368	14 1/2"	3.6	105	40	18
CV-368W		368	14 1/2"	4.8	105	50	22
CV-370W		370	14 9/16"	7.6	101	120	55
CV-380SW		380	15"	6.4	108	100	45
CV-380W		380	15"	7.6	105	120	55
CV-380LW		380	15"	8.0	105	120	55
CV-385W		385	15 3/16"	4.8	110	50	22
CV-400SW		400	15 3/4"	2.5	116	18	8
CV-400W		400	15 3/4"	4.6	116	50	22
CV-432W		432	17"	4.8	125	50	22
CV-450MW		450	17 3/4"	4.8	131	50	22
CV-450W		450	17 3/4"	8.0	128	120	55
CV-450LW		450	17 3/4"	9.0	128	175	80
CV-500W		500	19 11/16"	4.8	147	50	22
CV-500LW		500	19 11/16"	8.0	143	120	55
CV-550SW		550	21 11/16"	4.8	162	50	22
CV-550W		550	21 11/16"	8.0	160	120	55
CV-550DW		550	21 11/16"	9.0	160	175	80
CV-550LW		550	21 11/16"	12.7	159	250	114
CV-610SW		610	24"	4.8	181	50	22
CV-610MW		610	24"	7.6	177	120	55
CV-610W		610	24"	9.0	177	175	80
CV-635SW		635	25"	4.8	189	50	22
CV-685W		685	27"	9.0	202	175	80
CV-710W		710	28"	9.0	209	175	80
NEW CV-730SW		730	28 3/4"	4.8	219	50	22
CV-750W		750	29 1/2"	7.5	223	120	55
CV-762W		762	30"	9.0	227	175	80
CV-812W		812	32"	9.0	243	175	80
CV-914SW		914	36"	4.8	278	50	22
CV-914W		914	36"	9.0	275	175	80
CV-940W		940	37"	9.0	284	175	80
CV-1168W		1168	46"	9.0	356	175	80
CV-1219W		1219	48"	9.0	372	175	80
CV-1500W		1500	59"	9.0	462	175	80

配线槽

配线标志

扎线带

结束带

固定座

固定头、浪管

保护部品

接线头

套管

固定夹

PC板部品

扣具